
Serp is a modular backless bench system formed by six models with different radii, which can be added to others to form long zigzag bench arrangements, with and without LED lighting. Its rounded ends permit the installation of continuity modules, with no specific requirements in terms of precision. In the Serp Comfort version, the modules have a recessed teak wood seat.

Concrete | Modular | 2 243 cm/max | 1 1520 kg | 1 4

Add-ons: 🔄 | 🔓 | LED

C Update 03.07.2023





Origin

The Serp Comfort modular backless bench was first used in the elevated square of the Diagonal Mar shopping mall in Barcelona, where the LED lighting was first incorporated into the standard grooves provided for that purpose.

Modular


Different aggregations to the *Serp* modular backless bench system permit the creation of straight or undulated continuous backless benches. It can also be used to retain earth and form a boundary between areas with plants and areas frequented by pedestrians.

Material

The modules, with a square cross section of 50 x 50 cm and gently rounded edges, are made from dry mix concrete with an etched and water-repellent finish, in the *Escofet* standard chart colours.

Installation

Due to its heavy weight, it rests subtly on the ground or paving, with no need for anchors. Each module has two supporting legs that permit the passage of transportation slings to lift it from the ground, thus facilitating rainwater drainage.











1. Modular backless benches

Serp	Serp 1 R100	Serp 2 R185	Serp 3 R1185	Serp 4 R1915	Serp 5 Recto	Serp 6 R150
Dimensions	243x92x54 cm	223x72x54 cm	253x56x54 cm	224x54x54 cm	225x50x54 cm	199x70x54 cm
Weight	1430 kg	1244 kg	1486 kg	1327 kg	1345 kg	1094 kg
Lighting	LED strip 15 W/m 3000° K / 6000° K					
	0.474.4.5.4.170.7					

Driver 24 V / 1,5A / IP67

1.1 General features

Material	Reinforced concrete	Fixing	Free-standing
Finish	Etched and waterproofed		
Seat	Teak Wood		

Colours






A. Teak


1.2 Installation system

Hoisting

(W= 1430 kg / 1244 kg / 1486 kg / 1327 kg / 1345 kg / 1094 kg)



















Serp Comfort R100












Serp R100 LED


Serp Comfort R100 LED







243,4









FRONT














\$

Serp Comfort R185











Serp R185 LED


Power supply BOTTOM


222,6







Serp Comfort R185 LED




















Serp Comfort R1185







Serp R1185 LED


20 6 Power supply BOTTOM







Serp Comfort R1185 LED











Serp Comfort R1915




Serp R1915 LED



R1915 -


25


Serp Comfort R1915 LED





Serp Recto







Concrete inspection hatch available on both sides


TOP


Serp Comfort Recto







Serp Recto LED










Serp Comfort Recto LED











SIDE







Serp Comfort R150



Serp R150 LED



Serp Comfort R150 LED
















LED				
Operating voltage	24V			
Power	15 W/m			
Color temperature	3000K-6000K			
Degree of protection	IP67			

Driver Vossloh or similar				
Voltage	220-240V			
Frequency	50-60Hz			
Power factor	>0,9			
Degree of protection	IP67			




1.5 Aggregations

①R100 ②R185 ③R1185 ④R1915 ⑤RECTO ⑥R150











Warranty

5 years in concrete elements.

The names, trademarks and industrial models of the products have been logged in the corresponding registers. The technical information provided by Escofet about its products can be modified without prior notice.

Escofet 1886 S.A Head office and production

Montserrat, 162 E 08760 Martorell Barcelona - España T. 0034 937 737 150 F. 0034 937 737 151

info@escofet.com
www.escofet.com









